



NACHI BEARING INDIA PRIVATE LTD.

SRS9WMC1+[40-1000/1]L[H,P]M THK Miniature Linear Guide Caged Ball SRS Series

Bearing No. SRS9WMC1+[40-1000/1]L[H,P]M

SRS9WMC1+[40-1000/1]L[H,P]M Bearing 2D
drawings and 3D CAD models

| | |
|--|------------------------------|
| Days to Ship | 19 Days |
| Block Type | [Standard] M: Compact |
| The number of LM blocks combined with a axis | 1 |
| Nominal Part Number | 9W |
| Rail Type | Wide Rail |
| Rail Width W1 | 18 mm |
| Mounting Height M | 12 mm |
| Rail Length L | 40 ~ 1000 mm |
| Radial Clearance | Light Preload |
| Accuracy Grade | High Grade / Precision Grade |
| Rolling Element | Ball |
| Basic Load Rating Dynamic Rating C(N) | 3290 |
| Basic Load Rating Static Rating Co(N) | 3340 |
| Allowable Static Moment MA(N m) | 14 |
| Allowable Static Moment MB(N m) | 16.2 |
| Allowable Static Moment MC(N m) | 31.5 |
| Symbols for Dust Resistance | None (Not Recommended) |
| Block external dimension W | 30 mm |
| Block external dimension L | 39 mm |
| Number of Block Mounting | 4 |



NACHI BEARING INDIA PRIVATE LTD.

| | |
|---------------------------------|--------|
| Holes(holes) | |
| Mounting Hole Dimension S(M) | M3 |
| Mounting Hole Screw Depth | 2.8 mm |
| Block dimension L1 | 27 mm |