



NACHI BEARING INDIA PRIVATE LTD.

3RSR14WVM+[65-1800/1]L[H,P]M THK Miniature Linear Guide Full Ball RSR Series

Bearing No. 3RSR14WVM+[65-1800/1]L[H,P]M

3RSR14WVM+[65-1800/1]L[H,P]M Bearing 2D
drawings and 3D CAD models

Days to Ship	77 Days
Block Type	[Standard] M: Compact
The number of LM blocks combined with a axis	3
Nominal Part Number	14W
Rail Type	Wide Rail
Rail Width W1	30 mm
Mounting Height M	15 mm
Radial Clearance	Normal
Accuracy Grade	High Grade / Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	6010
Basic Load Rating Static Rating Co(N)	9080
Allowable Static Moment MA(N m)	43.2
Allowable Static Moment MB(N m)	38.2
Allowable Static Moment MC(N m)	110
Block Mounting Hole Pitch (Width Direction)	35 mm
Block Mounting Hole Pitch (Length Direction)	18 mm
Block Mounting Hole Diameter	4



NACHI BEARING INDIA PRIVATE LTD.

Rail Mounting Hole Pitch	40 mm
Rail Mounting Hole Diameter	4.5
Block external dimension W	50 mm
Block external dimension L	50 mm
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M4
Mounting Hole Screw Depth	4.5 mm
Block dimension L1	34.3 mm