



NACHI BEARING INDIA PRIVATE LTD.

SSR25XTB[1,2,3,4,5,6,7,8,9]C
 1+[96-3000/1]LY THK Linear Guide Caged Ball
 Radial SSR Accuracy and Preload Selectable

Bearing No.
 SSR25XTB[1,2,3,4,5,6,7,8,9]C1+[96-3000/1]LY

SSR25XTB[1,2,3,4,5,6,7,8,9]C1+[96-3000/1]LY Bearing 2D drawings and 3D CAD models

| | |
|--|---------------------------------|
| Days to Ship | 3 Days |
| Block Type | [Wide] TB: Flanged w/Thru Holes |
| The number of LM blocks combined with a axis | 1 ~ 9 |
| Nominal Part Number | 25 |
| Rail Width W1 | 23 mm |
| Mounting Height M | 33 mm |
| Material | Carbon Steel |
| Rail Length L | 96 ~ 3000 mm |
| Radial Clearance | Light Preload |
| Accuracy Grade | Normal Grade (Best Leadtime) |
| Rolling Element | Ball |
| Basic Load Rating Dynamic Rating C(N) | 31500 |
| Basic Load Rating Static Rating Co(N) | 36400 |
| Allowable Static Moment MA(N m) | 258 |
| Allowable Static Moment MB(N m) | 158 |
| Allowable Static Moment MC(N m) | 330 |
| Block external dimension W | 73 mm |



NACHI BEARING INDIA PRIVATE LTD.

| | |
|--|------------|
| Block external dimension L | 83 mm |
| Mounting hole for blocks | Thru Holes |
| Number of Block Mounting Holes(holes) | 4 |
| Mounting Hole Dimension H(\varnothing) | 7 |
| Mounting Hole Screw Depth | Through mm |
| Block dimension L1 | 59.8 mm |